(continuation sheet)

Hole Number: 156MW5

Project: VAFB Site 50

Geologist: C. Rohlfing

Sheet 2 of 2 Sheets

Elev (ft)	Depth (ft) bgs	Recovery (ft)	Description of Materials	USCS/ Litho	Field PID Results	Geotech. Sample or Core Box No.	Analytical Sample	Remarks
			From cuttings:					
			Sandy Silt - dark brown to reddish brown; 60% silt; 30% fine sand; 10% medium sand; subangular to subround; moist, no hydrocarbon odor.	SM/SDSL	<10			
	5		Silty sand with gravel - gray to dark brown; 60% fine sand; 10% medium sand; subangular to subround; 15% fine gravel; angular to round; 15% silt; lithic fragments; dry, very dense; no hydrocarbon odor.	SM/SDSL	<10			
	10		Silty Sand - gray to yellowish brown; 60% fine sand; 25% medium sand; subangular to round; 15% silt; moist; very dense; no hydrocarbon odor.	SM/SDSL	<10			
	15		Sandy Silt - gray to greenish gray with reddish brown mottling; 70% silt; 30% fine sand; subangular to subround; moist; soft; no hydrocarbon odor.	ML/SDSL	<10			groundwater at app. 18.5 feet bgs
	20		Sandy Clay - light gray to brown with reddish brown mottling; 90% medium plasticity clay; 10% fine sand; subangular to subround; moist; firm; no hydrocarbon odor.	CL/SDCL	<10			
	25		Sandy Silt - greenish gray to gray; 70% silt; 30% fine sand; subangular to subround; moist; firm; no hydrocarbon odor.	ML/SDSL	<10			
			Total depth = 25 feet bgs					
	30							
	35							
	40							
	45							
	50							

Project VAFB Site 50, AOC156