APPLIED ENVIRONMENTAL TECHNOLOGIES, INC.

Date: 04/03/2001

Sheet 1 of 1 **MW-9**

Job#: 0693-01A Location: 2520 Temple Street, Los Angeles

Drilling Company: APEX

Client: Sandra Sholkoff

Drilling Crew: Gerry, Shannon, and Nathan

Geologist: Lorien I. Sanders

Drilling Method: Hollow Stem Auger

Time Start/Finish: 12:25/13:50

Sampling Method: CA Split Sooon

Water Levels/Time/Date:

Surface Conditions: Dirt

Construction Details: 2" PVC 5' Blank, 20' Screen (0.02" Slots)

Depth In Feet	Sample Depth	Moisture Content	OVM ppm*	USCS Code	DESCRIPTION
0					Dirt.
1					
2					
3					
4					
5	5.0'	wet	24	CL	SILTY CLAY (CL), dark brown, soft (1/2/3), wet, very poorly graded.
6	(12:45)				Color change at 5.0' to dark gray.
7					
8					
9					
10	10.0'	wet	1,937		SILTY CLAY (CL), grayish-brown, stiff (3/4/5), wet, very poorly graded, moderate odor.
11	(12:55)				
12					
13					
14					
15	15.0'	dry/wet	87		CLAY (CL), medium brown, very stiff (6/13/17), dry to wet.
16	(13:00)				
17					
18					
19					
20	20.0'	dry	0		CLAY (CL), light brown, very stiff to hard (12/16/20), dry.
21	(13:05)				
22					
23					
24					
25	25.0'	dry/wet	0		SANDY SILTY CLAY (CL), light brown, very stiff to hard (12/16/20), dry to wet.
26	(13:15)				
27					Boring terminated at 25.0'; 14.0' water in hole during well construction.
28					
29					
30					
31					
32					
33					
34					
35					
36					
37					
38					
39					
40					

* - OVM concentrations related to hexane.