LOCATION MAP

NORTHING EASTING ELEVATION MW-10

[illegible]CIFIC ENVIRONMENTAL GRO[illegible] INC.

WELL/BORING NO. MW-10
PAGE 1 OF 1

PROJECT NO. 305-30.01
LOGGED BY: DA
DRILLER: Clearhaut
DRILLING METHOD: HSA
SAMPLING METHOD: Calmoc
CASING TYPE: Sch 40 pvc
SLOT SIZE: .010
GRAVEL PACK: 2/12 [illegible]

CLIENT: [illegible]
DATE DRILLED: [illegible]
LOCATION: [illegible]
HOLE DIAMETER: 10"
HOLE DEPTH: 16.5'
WELL DIAMETER: [illegible]
WELL DEPTH: 15'
CASING STICKUP: None

WELL COMPLETION	MOISTURE CONTENT	PID	PENETRATION (BLOWS/6")	DEPTH (FEET)	RECOVERY	SAMPLE INTERVAL	GRAPHIC	SOIL TYPE	LITHOLOGY / REMARKS
bentonite grout									Asphalt
				1					
	MST			2				GP	Sandy gravel; dark brown; fine to medium sand; medium to coarse well rounded gravel; dense; FPO
				3					
	wet								
				4					Clayey sand; dark grey to brown; 20-30% roots; 20-30% [illegible]; fine to medium [illegible]; loose; [illegible]
	SAT	4	3	5					
			1					SP	
			1	6					Sand; dark grey; fine to very fine sand; 10-15% silt; very loose; N-FPO
				7					
2/12 sand				8					
				9					
			6						@10'; 15-20% silt; loose; NPO
	Sat	6	3	10					
			3	11					
				12					
				13					
				14					
	Sat	3	3	15					@15'; 5-10% silt; dense; NPO
			5						
			11	16					
				17					
				18					
				19					
				20					