WELL NO. 15MW12

COORDINATES N 2120239.88
E 5780282.67

FIELD ENGINEER B. Sibbett DATE BEGAN 10/13/00
EDITED BY B. Sibbett DATE FINISHED 10/13/00
CHECKED BY _____ GROUND SURFACE EL. 61.32

DEPTH IN FEET	OVA READING (ppm)	LABORATORY TEST DATA: PERMEABILITY (cm/s)	BENZENE (ppm)	TOLUENE (ppm)	XYLENE (ppm)	TOTAL PETROLEUM HYDROCARBONS (ppm)	WELL SUMMARY/ BACKFILL	PENETRATION RESISTANCE (BLOWS/6 INCHES) SAMPLE	USCS	PROFILE	DESCRIPTION
0											
5											Dark yellowish brown (10YR 3/4) SAND, dry, medium grained, wel sorted.
10								DW0032	SP		Brownish yellow (10YR 6/6) SAND, damp, medium grained, very well sorted.
15											
20								DW0033 4 14 26 37			Groundwater measured at 20.9 ft. on 11/08/00 Yellowish brown (10YR 5/6) SAND, wet, medium grained, very well sorted.
25											
30											Flowing sand, no sample.
35								7 13 20 40	SP		Sample lost in hole.
40											Drilling soft sand.
45											SAND to 45 ft. 45.0'
											SHALE, BEDROCK at 45 feet, dark gray (5Y 3/1) green tint.
50											TOTAL DEPTH = 46.5 FEET
55											
60											
65											
70											

PROJECT NO. 779480-3D210691
CLIENT: Site 15 Vandenberg AFB

SEE LEGEND FOR LOGS AND TEST PITS
FOR EXPLANATION OF SYMBOLS AND TERMS

INTERNATIONAL TECHNOLOGY CORPORATION