ENVIRONMENTAL RESOLUTIONS, INC.

BORING LOG DP4

(Page 1 of 2)

Date Drilled:	: 04/25/06
Drilling Co.:	: Woodward Drilling
Drilling Method:	: GeoProbe
Sampling Method:	: Continuous Core
Borehole Diameter:	: 2"
Casing Diameter:	: N/A
Location N-S	:
Location E-W	:
Total Depth:	: 36' bgs
First GW Depth:	: 13' bgs

Project No.:	: Former Exxon Service Station 7-0249
Site:	: 6301 Commerce Boulevard, Rohnert Park, California
Logged By:	: Vicki Burns
Reviewed By:	: Geoffrey V. Waterhouse, P.G. 5019
Signature:	:

Sample Condition
- No Recovery
- Sampled Interval
- Described Sample
- Preserved Sample

Water Levels
- Upper water bearing zone: 13' bgs
- Lower water bearing zone: 27' bgs

Boring: DP4

Depth (ft)	Blow Count	OVM/PID (ppmv)	Sample	Column	USCS	DESCRIPTION
0						6" Asphalt
					CH	CLAY: dark gray, moist, high plasticity
5		1.1				
					CH	CLAY WITH SAND: dark gray, moist, high plasticity, fine-grained sand
					CL	SANDY CLAY: olive gray, damp, low plasticity, ~20-30% very fine-grained sand Cleared to 8 fbgs using air-knife and hand auger, 4/3/06
10		0.2			CL	SANDY CLAY: olive gray, damp, low plasticity, ~15-20% very fine-grained sand, with powdery calcium carbonate
					SP	SAND WITH SILT: very fine- to medium-grained, brown, moist to wet, poorly graded
15		0.3			CL	CLAY: light grayish brown, moist, moderate plasticity, with trace sand @17'- 20': with calcium carbonate nodules to 0.1" diameter
20						

Neat Cement

06-21-2006 J:\2002\BORING LOGS\DP4.bor

ENVIRONMENTAL RESOLUTIONS, INC.

BORING LOG DP4

(Page 2 of 2)

Date Drilled:	: 04/25/06
Drilling Co.:	: Woodward Drilling
Drilling Method:	: GeoProbe
Sampling Method:	: Continuous Core
Borehole Diameter:	: 2"
Casing Diameter:	: N/A
Location N-S	:
Location E-W	:
Total Depth:	: 36' bgs
First GW Depth:	: 13' bgs

Project No.:	: Former Exxon Service Station 7-0249
Site:	: 6301 Commerce Boulevard, Rohnert Park, California
Logged By:	: Vicki Burns
Reviewed By:	: Geoffrey V. Waterhouse, P.G. 5019
Signature:	:

Sample Condition
- No Recovery
- Sampled Interval
- Described Sample
- Preserved Sample

Water Levels
- Upper water bearing zone: 13' bgs
- Lower water bearing zone: 27' bgs

Boring: DP4

Depth (ft)	Blow Count	OVM/PID (ppmv)	Sample	Column	USCS	DESCRIPTION
20		1.4			CL	CLAY WITH SAND: light grayish brown, moist, moderate plasticity
					CL	CLAY: light grayish brown, moist, moderate plasticity, with trace sand
25		2.0			CL	SANDY CLAY: yellowish brown, moist to wet, low to medium plasticity
					SM	SILTY SAND: fine-grained, dark gray, moist, poorly graded, ~25% silt
					SP	SAND: fine- to medium-grained, dark gray, saturated, trace clay @26.5' - 27: medium-to course-grained sand
					CL	SANDY CLAY: dark gray, moist to wet, medium plasticity,~40% fine- to medium-grained sand
30		0.0			CH	CLAY: dark greenish gray, moist, high plasticity, trace sand
35		0.0				
40						

Neat Cement

Total depth @ 36' bgs 09:45 4/25/06
Free water encountered @13' bgs

06-21-2006 J:\2002\BORING LOGS\DP4.bor